



HI-PRO® POLY BASE FIXED STUD GLIDES


The IEC High Profile Steel and Stainless Steel Poly Base Fixed Stud Glide features IEC's Ridge-Grip® design and is ideal for light and medium-duty load requirements. **The high-profile base is useful for raising kitchen equipment, furniture, grocery displays, fitness equipment, electronic equipment and other products for ease of cleaning, sweeping, mopping, ventilation, etc.** The stud will tilt several degrees under load to compensate for unlevel surfaces. Cost-effective for applications not requiring a swivel base. Zinc plated steel stud and black polypropylene base, 1" thick. Two base sizes to choose from (1-1/2" to 2"). Many sizes available with Top-A-Just® top-end external hex (-HX). You may also request top broached hex, allen drive (-BR).



Top-A-Just® (-HX)



Top-A-Just® (-BR)



Features

- High-profile base
- Ridge-Grip® design
- Loads to 3000 lbs
- Steel and Stainless studs
- Corrosion resistant
- RoHS compliant
- Top hex options

Applications

- Kitchen Equipment
- Displays
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic equipment
- Medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables

Steel	SS	Load	Thread	Hex	A	B	C
High Profile Steel and Stainless Steel Poly Base Fixed Stud Glides							
IL140-4Bx1/2	IL140-4BSx1/2	100	1/4-20	1/2	1-1/2	1/2	1-5/16
IL140-4Bx1	IL140-4BSx1	100	1/4-20	1/2	1-1/2	1	1-5/16
IL140-4B	IL140-4BS	100	1/4-20	1/2	1-1/2	1-9/16	1-5/16
IL140-4Bx2-HX	IL140-4BSx2-HX	100	1/4-20	1/2	1-1/2	2	1-5/16
IL140-4Bx25	IL140-4BSx25	100	1/4-20	1/2	1-1/2	2-1/2	1-5/16
IL140-5Bx3/4	IL140-5BSx3/4	500	5/16-18	1/2	1-1/2	3/4	1-5/16
IL140-5Bx15-HX	IL140-5BSx15-HX	500	5/16-18	1/2	1-1/2	1-1/2	1-5/16
IL140-5B	IL140-5BS	500	5/16-18	1/2	1-1/2	1-9/16	1-5/16
IL140-5Bx25-HX	IL140-5BSx25-HX	500	5/16-18	1/2	1-1/2	2-1/2	1-5/16
IL140-5Bx3	IL140-5BSx3	500	5/16-18	1/2	1-1/2	3	1-5/16
IL140-5Bx4	IL140-5BSx4	500	5/16-18	1/2	1-1/2	4	1-5/16
IL140-6Bx3/4	IL140-6BSx3/4	1000	3/8-16	1/2	1-1/2	3/4	1-5/16
IL140-6Bx15-HX	IL140-6BSx15-HX	1000	3/8-16	1/2	1-1/2	1-1/2	1-5/16
IL140-6B	IL140-6BS	1000	3/8-16	1/2	1-1/2	1-9/16	1-5/16
IL140-6Bx1	IL140-6BSx1	1000	3/8-16	1/2	1-1/2	1	1-5/16
IL140-6Bx2	IL140-6BSx2	1000	3/8-16	1/2	1-1/2	2	1-5/16
IL140-6Bx2-HX	IL140-6BSx2-HX	1000	3/8-16	1/2	1-1/2	2	1-5/16
IL140-6Bx3	IL140-6BSx3	1000	3/8-16	1/2	1-1/2	3	1-5/16
IL140-6Bx3-HX	IL140-6BSx3-HX	1000	3/8-16	1/2	1-1/2	3	1-5/16
IL140-6Bx4	IL140-6BSx4	1000	3/8-16	1/2	1-1/2	4	1-5/16
IL140-6Bx45-HX	IL140-6BSx45-HX	1000	3/8-16	1/2	1-1/2	4-1/2	1-5/16
IL140-6Bx6-HX	IL140-6BSx6-HX	1000	3/8-16	1/2	1-1/2	6	1-5/16
IL140-6FBx1	IL140-6FBSx1	1000	3/8-24	1/2	1-1/2	1	1-5/16
IL140-6FBx2	IL140-6FBSx2	1000	3/8-24	1/2	1-1/2	2	1-5/16
IL140-7B	IL140-7BS	2000	1/2-13	1/2	1-1/2	1-9/16	1-5/16
IL140-7Bx2	IL140-7BSx2	2000	1/2-13	1/2	1-1/2	2	1-5/16
IL140-7Bx2-HX	IL140-7BSx2-HX	2000	1/2-13	1/2	1-1/2	2	1-5/16
IL140-7Bx25-HX	IL140-7BSx25-HX	2000	1/2-13	1/2	1-1/2	2-1/2	1-5/16
IL140-7Bx3	IL140-7BSx3	2000	1/2-13	1/2	1-1/2	3	1-5/16
IL140-7Bx3-HX	IL140-7BSx3-HX	2000	1/2-13	1/2	1-1/2	3	1-5/16
IL140-7Bx35-HX	IL140-7BSx35-HX	2000	1/2-13	1/2	1-1/2	3-1/2	1-5/16
IL140-7Bx4	IL140-7BSx4	2000	1/2-13	1/2	1-1/2	4	1-5/16
IL140-7Bx4-HX	IL140-7BSx4-HX	2000	1/2-13	1/2	1-1/2	4	1-5/16
IL140-7Bx5	IL140-7BSx5	2000	1/2-13	1/2	1-1/2	5	1-5/16
IL140-7Bx5-HX	IL140-7BSx5-HX	2000	1/2-13	1/2	1-1/2	5	1-5/16
IL140-7Bx6-HX	IL140-7BSx6-HX	1500	1/2-13	1/2	1-1/2	6	1-5/16
IL140-7Bx8-HX	IL140-7BSx8-HX	1000	1/2-13	1/2	1-1/2	8	1-5/16
IL140-7FBx1	IL140-7FBSx1	2000	1/2-20	1/2	1-1/2	1	1-5/16
IL140-7FBx2	IL140-7FBSx2	2000	1/2-20	1/2	1-1/2	2	1-5/16
IL140-7FBx4	IL140-7FBSx4	2000	1/2-20	1/2	1-1/2	4	1-5/16
IL140-8B	IL140-8BS	2500	5/8-11	5/8	1-1/2	1-9/16	1-5/16
IL140-8Bx3	IL140-8BSx3	2500	5/8-11	5/8	1-1/2	3	1-5/16
IL140-8Bx4	IL140-8BSx4	2500	5/8-11	5/8	1-1/2	4	1-5/16
IL140-8Bx5	IL140-8BSx5	2500	5/8-11	5/8	1-1/2	5	1-5/16
IL140-9B	IL140-9BS	3000	3/4-10	3/4	1-1/2	1-9/16	1-5/16
IL140-9Bx3	IL140-9BSx3	3000	3/4-10	3/4	1-1/2	3	1-5/16
IL140-9Bx4	IL140-9BSx4	3000	3/4-10	3/4	1-1/2	4	1-5/16



HI-PRO® POLY BASE FIXED STUD GLIDES


The IEC High Profile Steel and Stainless Steel Poly Base Fixed Stud Glide features IEC's Ridge-Grip® design and is ideal for light and medium-duty load requirements. **The high-profile base is useful for raising kitchen equipment, furniture, grocery displays, fitness equipment, electronic equipment and other products for ease of cleaning, sweeping, mopping, ventilation, etc.** The stud will tilt several degrees under load to compensate for unlevel surfaces. Cost-effective for applications not requiring a swivel base. Zinc plated steel stud and black polypropylene base, 1" thick. Two base sizes to choose from (1-1/2" to 2"). Many sizes available with Top-A-Just® top-end external hex (-HX). You may also request top broached hex, allen drive (-BR).



Top-A-Just® (-HX)



Top-A-Just® (-BR)



Features

- High-profile base
- Ridge-Grip® design
- Loads to 3000 lbs
- Steel and Stainless studs
- Corrosion resistant
- RoHS compliant
- Top hex options

Applications

- Kitchen Equipment
- Displays
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic equipment
- Medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables

Steel	SS	Load	Thread	Hex	A	B	C
High Profile Steel and Stainless Steel Poly Base Fixed Stud Glides							
IL141-4Bx1/2	IL141-4BSx1/2	100	1/4-20	1/2	2	1/2	1-5/16
IL141-4Bx1	IL141-4BSx1	100	1/4-20	1/2	2	1	1-5/16
IL141-4B	IL141-4BS	100	1/4-20	1/2	2	1-9/16	1-5/16
IL141-4Bx2-HX	IL141-4BSx2-HX	100	1/4-20	1/2	2	2	1-5/16
IL141-4Bx25	IL141-4BSx25	100	1/4-20	1/2	2	2-1/2	1-5/16
IL141-5Bx3/4	IL141-5BSx3/4	500	5/16-18	1/2	2	3/4	1-5/16
IL141-5Bx15-HX	IL141-5BSx15-HX	500	5/16-18	1/2	2	1-1/2	1-5/16
IL141-5B	IL141-5BS	500	5/16-18	1/2	2	1-9/16	1-5/16
IL141-5Bx25-HX	IL141-5BSx25-HX	500	5/16-18	1/2	2	2-1/2	1-5/16
IL141-5Bx3	IL141-5BSx3	500	5/16-18	1/2	2	3	1-5/16
IL141-5Bx4	IL141-5BSx4	500	5/16-18	1/2	2	4	1-5/16
IL141-6Bx3/4	IL141-6BSx3/4	1000	3/8-16	1/2	2	3/4	1-5/16
IL141-6Bx15-HX	IL141-6BSx15-HX	1000	3/8-16	1/2	2	1-1/2	1-5/16
IL141-6B	IL141-6BS	1000	3/8-16	1/2	2	1-9/16	1-5/16
IL141-6Bx1	IL141-6BSx1	1000	3/8-16	1/2	2	1	1-5/16
IL141-6Bx2	IL141-6BSx2	1000	3/8-16	1/2	2	2	1-5/16
IL141-6Bx2-HX	IL141-6BSx2-HX	1000	3/8-16	1/2	2	2	1-5/16
IL141-6Bx3	IL141-6BSx3	1000	3/8-16	1/2	2	3	1-5/16
IL141-6Bx3-HX	IL141-6BSx3-HX	1000	3/8-16	1/2	2	3	1-5/16
IL141-6Bx4	IL141-6BSx4	1000	3/8-16	1/2	2	4	1-5/16
IL141-6Bx45-HX	IL141-6BSx45-HX	1000	3/8-16	1/2	2	4-1/2	1-5/16
IL141-6Bx6-HX	IL141-6BSx6-HX	1000	3/8-16	1/2	2	6	1-5/16
IL141-6FBx1	IL141-6FBSx1	1000	3/8-24	1/2	2	1	1-5/16
IL141-6FBx2	IL141-6FBSx2	1000	3/8-24	1/2	2	2	1-5/16
IL141-7B	IL141-7BS	2000	1/2-13	1/2	2	1-9/16	1-5/16
IL141-7Bx2	IL141-7BSx2	2000	1/2-13	1/2	2	2	1-5/16
IL141-7Bx2-HX	IL141-7BSx2-HX	2000	1/2-13	1/2	2	2	1-5/16
IL141-7Bx25-HX	IL141-7BSx25-HX	2000	1/2-13	1/2	2	2-1/2	1-5/16
IL141-7Bx3	IL141-7BSx3	2000	1/2-13	1/2	2	3	1-5/16
IL141-7Bx3-HX	IL141-7BSx3-HX	2000	1/2-13	1/2	2	3	1-5/16
IL141-7Bx35-HX	IL141-7BSx35-HX	2000	1/2-13	1/2	2	3-1/2	1-5/16
IL141-7Bx4	IL141-7BSx4	2000	1/2-13	1/2	2	4	1-5/16
IL141-7Bx4-HX	IL141-7BSx4-HX	2000	1/2-13	1/2	2	4	1-5/16
IL141-7Bx5	IL141-7BSx5	2000	1/2-13	1/2	2	5	1-5/16
IL141-7Bx5-HX	IL141-7BSx5-HX	2000	1/2-13	1/2	2	5	1-5/16
IL141-7Bx6-HX	IL141-7BSx6-HX	1500	1/2-13	1/2	2	6	1-5/16
IL141-7Bx8-HX	IL141-7BSx8-HX	1000	1/2-13	1/2	2	8	1-5/16
IL141-7FBx1	IL141-7FBSx1	2000	1/2-20	1/2	2	1	1-5/16
IL141-7FBx2	IL141-7FBSx2	2000	1/2-20	1/2	2	2	1-5/16
IL141-7FBx4	IL141-7FBSx4	2000	1/2-20	1/2	2	4	1-5/16
IL141-8B	IL141-8BS	2500	5/8-11	5/8	2	1-9/16	1-5/16
IL141-8Bx3	IL141-8BSx3	2500	5/8-11	5/8	2	3	1-5/16
IL141-8Bx4	IL141-8BSx4	2500	5/8-11	5/8	2	4	1-5/16
IL141-8Bx5	IL141-8BSx5	2500	5/8-11	5/8	2	5	1-5/16
IL141-9B	IL141-9BS	3000	3/4-10	3/4	2	1-9/16	1-5/16
IL141-9Bx3	IL141-9BSx3	3000	3/4-10	3/4	2	3	1-5/16
IL141-9Bx4	IL141-9BSx4	3000	3/4-10	3/4	2	4	1-5/16