



INTERNATIONAL EQUIPMENT COMPONENTS, INC.

Phone: 562.597.4533 eMail: sales@iec-corp.com

Web: www.iec-corp.com | www.levelingmounts.com

MEDIUM-DUTY LEVELERS

SAUCER BASE® FIXED SOCKET

Medium Duty Low-Profile, SAUCER BASE® Fixed Socket Levelers

The IEC Saucer Base® Fixed Socket Levelers have a curved bottom edge design for improved sliding capability and are ideal for medium duty, high volume applications. These levelers use advanced 3D engineering design. Eight (8) nylon base sizes to choose from: 3/4" to 4", 1/2" thick with a bottom hex drive molded into the base. Steel socket and washer have clear zinc plating.


Features

- Loads to 3000 lbs
- Corrosion resistant
- Bottom hex drive
- 8 base diameters
- Glass-filled nylon
- RoHS compliant
- Curved bottom edge for improved sliding
- Black base standard, to order wood brown, add -BN to p/n. To order metallic gray, add -GY to p/n.

Applications

- Conveyors
- Machinery
- Work tables

- Appliances
- Displays
- Racks
- Vending Machines
- Stages
- Decks
- Electronic equipment
- Enclosures



OPTIONAL BASE COLORS



LOW PROFILE FIXED — SOCKET LEVELERS

Steel	Stainless	Load	Thread	Hex	A	B	C	F
IL120-4B-T	IL120-4BS-T	100	1/4-20	1/2	3/4	1/4	3/4	1/4
IL120-5B-T	IL120-5BS-T	500	5/16-18	1/2	3/4	3/8	7/8	1/4
IL120-6B-T	IL120-6BS-T	1000	3/8-16	1/2	3/4	1/2	1	3/8
IL120-7B-T	IL120-7BS-T	2000	1/2-13	5/8	3/4	1/2	1	3/8
IL120-8B-T	IL120-8BS-T	3000	5/8-11	3/4	3/4	5/8	1-1/8	1/2
IL120-9B-T	IL120-9BS-T	3000	3/4-10	1	3/4	3/4	1-1/4	5/8
IL121-4B-T	IL121-4BS-T	100	1/4-20	1/2	1	1/4	3/4	1/4
IL121-5B-T	IL121-5BS-T	500	5/16-18	1/2	1	3/8	7/8	1/4
IL121-6B-T	IL121-6BS-T	1000	3/8-16	1/2	1	1/2	1	3/8
IL121-7B-T	IL121-7BS-T	2000	1/2-13	5/8	1	1/2	1	3/8
IL121-8B-T	IL121-8BS-T	3000	5/8-11	3/4	1	5/8	1-1/8	1/2
IL121-9B-T	IL121-9BS-T	3000	3/4-10	1	1	3/4	1-1/4	5/8
IL122-4B-T	IL122-4BS-T	100	1/4-20	1/2	1-1/4	1/4	3/4	1/4
IL122-5B-T	IL122-5BS-T	500	5/16-18	1/2	1-1/4	3/8	7/8	1/4
IL122-6B-T	IL122-6BS-T	1000	3/8-16	1/2	1-1/4	1/2	1	3/8
IL122-7B-T	IL122-7BS-T	2000	1/2-13	5/8	1-1/4	1/2	1	3/8
IL122-8B-T	IL122-8BS-T	3000	5/8-11	3/4	1-1/4	5/8	1-1/8	1/2
IL122-9B-T	IL122-9BS-T	3000	3/4-10	1	1-1/4	3/4	1-1/4	5/8
IL123-4B-T	IL123-4BS-T	100	1/4-20	1/2	1-1/2	1/4	3/4	1/4
IL123-5B-T	IL123-5BS-T	500	5/16-18	1/2	1-1/2	3/8	7/8	1/4
IL123-6B-T	IL123-6BS-T	1000	3/8-16	1/2	1-1/2	1/2	1	3/8
IL123-7B-T	IL123-7BS-T	2000	1/2-13	5/8	1-1/2	1/2	1	3/8
IL123-8B-T	IL123-8BS-T	3000	5/8-11	3/4	1-1/2	5/8	1-1/8	1/2
IL123-9B-T	IL123-9BS-T	3000	3/4-10	1	1-1/2	3/4	1-1/4	5/8
IL124-4B-T	IL124-4BS-T	100	1/4-20	1/2	1-3/4	1/4	3/4	1/4
IL124-5B-T	IL124-5BS-T	500	5/16-18	1/2	1-3/4	3/8	7/8	1/4
IL124-6B-T	IL124-6BS-T	1000	3/8-16	1/2	1-3/4	1/2	1	3/8
IL124-7B-T	IL124-7BS-T	2000	1/2-13	5/8	1-3/4	1/2	1	3/8
IL124-8B-T	IL124-8BS-T	3000	5/8-11	3/4	1-3/4	5/8	1-1/8	1/2
IL124-9B-T	IL124-9BS-T	3000	3/4-10	1	1-3/4	3/4	1-1/4	5/8
IL125-4B-T	IL125-4BS-T	100	1/4-20	1/2	2	1/4	3/4	1/4
IL125-5B-T	IL125-5BS-T	500	5/16-18	1/2	2	3/8	7/8	1/4
IL125-6B-T	IL125-6BS-T	1000	3/8-16	1/2	2	1/2	1	3/8
IL125-7B-T	IL125-7BS-T	2000	1/2-13	5/8	2	1/2	1	3/8
IL125-8B-T	IL125-8BS-T	3000	5/8-11	3/4	2	5/8	1-1/8	1/2
IL125-9B-T	IL125-9BS-T	3000	3/4-10	1	2	3/4	1-1/4	5/8
IL126-4B-T	IL126-4BS-T	100	1/4-20	1/2	3	1/4	3/4	1/4
IL126-5B-T	IL126-5BS-T	500	5/16-18	1/2	3	3/8	7/8	1/4
IL126-6B-T	IL126-6BS-T	1000	3/8-16	1/2	3	1/2	1	3/8
IL126-7B-T	IL126-7BS-T	2000	1/2-13	5/8	3	1/2	1	3/8
IL126-8B-T	IL126-8BS-T	3000	5/8-11	3/4	3	5/8	1-1/8	1/2
IL126-9B-T	IL126-9BS-T	3000	3/4-10	1	3	3/4	1-1/4	5/8
IL127-4B-T	IL127-4BS-T	100	1/4-20	1/2	4	1/4	3/4	1/4
IL127-5B-T	IL127-5BS-T	500	5/16-18	1/2	4	3/8	7/8	1/4
IL127-6B-T	IL127-6BS-T	1000	3/8-16	1/2	4	1/2	1	3/8
IL127-7B-T	IL127-7BS-T	2000	1/2-13	5/8	4	1/2	1	3/8
IL127-8B-T	IL127-8BS-T	3000	5/8-11	3/4	4	5/8	1-1/8	1/2
IL127-9B-T	IL127-9BS-T	3000	3/4-10	1	4	3/4	1-1/4	5/8