




HI-PRO VIBE-GLIDES®
Hi-Pro Socket Vibe-Glides®
 1-1/2" to 2" BASE DIAMETER



Hi-Pro Socket Vibe-Glides®

The IEC *high-profile non-threaded socket* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. It has a thru-hole to accept you own wood screw, machine screw or rivet, etc. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2".



Features

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- Oil and solvent resistant
- RoHS compliant

Applications

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Note: Distance from bottom of center hole to bottom of base = 5/16"

– Soft-Flex Hi-Pro Socket Vibe-Glides® (30-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-HPVG-THNT-30	125	11/32	1-1/2	11/16	1
IL84-HPVG-THNT-30	150	11/32	2	11/16	1

– Standard-Flex Hi-Pro Socket Vibe-Glides® (45-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-HPVG-THNT-45	450	11/32	1-1/2	11/16	1
IL84-HPVG-THNT-45	600	11/32	2	11/16	1

– Firm-Flex Hi-Pro Socket Vibe-Glides® (60-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-HPVG-THNT-60	750	11/32	1-1/2	11/16	1
IL84-HPVG-THNT-60	900	11/32	2	11/16	1

– Hard-Flex Hi-Pro Socket Vibe-Glides® (75-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-HPVG-THNT-75	1000	11/32	1-1/2	11/16	1
IL84-HPVG-THNT-75	1500	11/32	2	11/16	1

– Stiff-Flex Hi-Pro Socket Vibe-Glides® (90-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-HPVG-THNT-90	1000	11/32	1-1/2	11/16	1
IL84-HPVG-THNT-90	1500	11/32	2	11/16	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE			Standard-Flex® TPE			Firm-Flex® TPU			Hard-Flex® TPU			Stiff-Flex® TPU		
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)			Medium Hard (Pink Eraser) (Wiper Blades)			Hard (Tire Tread)			Extra Hard (Skate Wheel)					
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20	25 30 35	40 45 50	55 60 65	70 75 80	85 90 95	100									




HI-PRO VIBE-GLIDES®
Double Hi-Pro Socket Vibe-Glides®
 1-1/2" to 2" BASE DIAMETER - 2" TALL



Double Hi-Pro Socket Vibe-Glides®

The IEC *Double high-profile non-threaded socket* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design with a 2" base height. These glides are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. It has a thru-hole to accept you own wood screw, machine screw or rivet, etc. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2".



Features

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- Oil and solvent resistant
- RoHS compliant

Applications

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Note: Distance from bottom of center hole to bottom of base = 5/16"

- Soft-Flex Double Hi-Pro Socket Vibe-Glides® (30-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-DHPVG-THNT-30	125	11/32	1-1/2	11/16	2
IL84-DHPVG-THNT-30	150	11/32	2	11/16	2

- Standard-Flex Double Hi-Pro Socket Vibe-Glides® (45-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-DHPVG-THNT-45	450	11/32	1-1/2	11/16	2
IL84-DHPVG-THNT-45	600	11/32	2	11/16	2

- Firm-Flex Double Hi-Pro Socket Vibe-Glides® (60-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-DHPVG-THNT-60	750	11/32	1-1/2	11/16	2
IL84-DHPVG-THNT-60	900	11/32	2	11/16	2

- Hard-Flex Double Hi-Pro Socket Vibe-Glides® (75-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-DHPVG-THNT-75	1000	11/32	1-1/2	11/16	2
IL84-DHPVG-THNT-75	1500	11/32	2	11/16	2

- Stiff-Flex Double Hi-Pro Socket Vibe-Glides® (90-A Durometer)
Thru-Hole (Non-Threaded)

P/N	Load	Hole Size	A	B	C
High Profile Poly Base Thru-Hole Non-Threaded Socket Glides					
IL82-DHPVG-THNT-90	1000	11/32	1-1/2	11/16	2
IL84-DHPVG-THNT-90	1500	11/32	2	11/16	2

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU		Hard-Flex® TPU		Stiff-Flex® TPU	
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)		Medium Hard (Pink Eraser) (Wiper Blades)		Hard (Tire Tread)		Extra Hard (Skate Wheel)			
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20	25 30 35	40 45 50	55 60 65 70	75 80 85	90 95 100					