



**Soft-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



Vibration Glide Bottom

**– Soft-Flex Hi-Pro Vibe-Glides® (30-A Durometer) –**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL82-HPVG-4Bx1/4-30	IL82-HPVG-4BSx1/4-30	40	1/4-20	1-1/2	1/4	1
IL82-HPVG-4Bx1/2-30	IL82-HPVG-4BSx1/2-30	40	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx1/2-HX-SL-30		40	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx3/4-30	IL82-HPVG-4BSx3/4-30	40	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx3/4-HX-SL-30		40	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx1-30	IL82-HPVG-4BSx1-30	40	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx1-HX-SL-30		40	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx125-30	IL82-HPVG-4BSx125-30	40	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx125-HX-SL-30		40	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx150-30	IL82-HPVG-4BSx150-30	40	1/4-20	1-1/2	1-1/2	1
IL82-HPVG-4Bx175-30	IL82-HPVG-4BSx175-30	40	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx175-HX-SL-30		40	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx2-30	IL82-HPVG-4BSx2-30	40	1/4-20	1-1/2	2	1
IL82-HPVG-4Bx275-30	IL82-HPVG-4BSx275-30	40	1/4-20	1-1/2	2-3/4	1
IL82-HPVG-5Bx1/4-30	IL82-HPVG-5BSx1/4-30	40	5/16-18	1-1/2	1/4	1
IL82-HPVG-5Bx1/2-30	IL82-HPVG-5BSx1/2-30	40	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx1/2-HX-SL-30		40	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx3/4-30	IL82-HPVG-5BSx3/4-30	40	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx3/4-HX-SL-30		40	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx1-30	IL82-HPVG-5BSx1-30	40	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx1-HX-SL-30		40	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx125-HX-SL-30		40	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx125-30	IL82-HPVG-5BSx125-30	40	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx175-30	IL82-HPVG-5BSx175-30	40	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx175-HX-SL-30		40	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx225-HX-SL-30		40	5/16-18	1-1/2	2-1/4	1
IL82-HPVG-6Bx1/4-30	IL82-HPVG-6BSx1/4-30	40	3/8-16	1-1/2	1/4	1
IL82-HPVG-6Bx1/2-30	IL82-HPVG-6BSx1/2-30	40	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx1/2-HX-SL-30		40	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx3/4-HX-SL-30		40	3/8-16	1-1/2	3/4	1
IL82-HPVG-6Bx1-30	IL82-HPVG-6BSx1-30	40	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx1-HX-SL-30		40	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx125-30	IL82-HPVG-6BSx125-30	40	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx125-HX-SL-30		40	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx150-30	IL82-HPVG-6BSx150-30	40	3/8-16	1-1/2	1-1/2	1
IL82-HPVG-6Bx175-HX-SL-30		40	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx175-30	IL82-HPVG-6BSx175-30	40	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx238-30	IL82-HPVG-6BSx238-30	40	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-SL-30		40	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-HX-SL-30		40	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx275-HX-SL-30		40	3/8-16	1-1/2	2-3/4	1
IL82-HPVG-6Bx338-HX-SL-30		40	3/8-16	1-1/2	3-3/8	1
IL82-HPVG-7Bx3/4-30	IL82-HPVG-7BSx3/4-30	40	1/2-13	1-1/2	3/4	1
IL82-HPVG-7Bx1-30	IL82-HPVG-7BSx1-30	40	1/2-13	1-1/2	1	1
IL82-HPVG-7Bx125-30	IL82-HPVG-7BSx125-30	40	1/2-13	1-1/2	1-1/4	1
IL82-HPVG-7Bx150-30	IL82-HPVG-7BSx150-30	40	1/2-13	1-1/2	1-1/2	1
IL82-HPVG-7Bx2-30	IL82-HPVG-7BSx2-30	40	1/2-13	1-1/2	2	1
IL82-HPVG-7Bx238-30		40	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx238-HX-30		40	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx278-30	IL82-HPVG-7BSx278-30	40	1/2-13	1-1/2	2-7/8	1
IL82-HPVG-7Bx3-HX-30		40	1/2-13	1-1/2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings	Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU		Hard-Flex® TPU		Stiff-Flex® TPU										
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser)		Medium Hard (Wiper Blades)		Hard (Tire Tread)		Extra Hard (Skate Wheel)										
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100

Copyright © 2019 IEC, Inc.



**HI-PRO VIBE-GLIDES®**

**Soft-Flex Hi-Pro Vibe-Glides®**

1-1/2" to 2" BASE DIAMETER

**Soft-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



Vibration Glide Bottom

**- Soft-Flex Hi-Pro Vibe-Glides® (30-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL84-HPVG-4Bx1/4-30	IL84-HPVG-4BSx1/4-30	50	1/4-20	2	1/4	1
IL84-HPVG-4Bx1/2-30	IL84-HPVG-4BSx1/2-30	50	1/4-20	2	1/2	1
IL84-HPVG-4Bx1/2-HX-SL-30		50	1/4-20	2	1/2	1
IL84-HPVG-4Bx3/4-30	IL84-HPVG-4BSx3/4-30	50	1/4-20	2	3/4	1
IL84-HPVG-4Bx3/4-HX-SL-30		50	1/4-20	2	3/4	1
IL84-HPVG-4Bx1-30	IL84-HPVG-4BSx1-30	50	1/4-20	2	1	1
IL84-HPVG-4Bx1-HX-SL-30		50	1/4-20	2	1	1
IL84-HPVG-4Bx125-30	IL84-HPVG-4BSx125-30	50	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx125-HX-SL-30		50	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx150-30	IL84-HPVG-4BSx150-30	50	1/4-20	2	1-1/2	1
IL84-HPVG-4Bx175-30	IL84-HPVG-4BSx175-30	50	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx175-HX-SL-30		50	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx2-30	IL84-HPVG-4BSx2-30	50	1/4-20	2	2	1
IL84-HPVG-4Bx275-30	IL84-HPVG-4BSx275-30	50	1/4-20	2	2-3/4	1
IL84-HPVG-5Bx1/4-30	IL84-HPVG-5BSx1/4-30	50	5/16-18	2	1/4	1
IL84-HPVG-5Bx1/2-30	IL84-HPVG-5BSx1/2-30	50	5/16-18	2	1/2	1
IL84-HPVG-5Bx1/2-HX-SL-30		50	5/16-18	2	1/2	1
IL84-HPVG-5Bx3/4-30	IL84-HPVG-5BSx3/4-30	50	5/16-18	2	3/4	1
IL84-HPVG-5Bx3/4-HX-SL-30		50	5/16-18	2	3/4	1
IL84-HPVG-5Bx1-30	IL84-HPVG-5BSx1-30	50	5/16-18	2	1	1
IL84-HPVG-5Bx1-HX-SL-30		50	5/16-18	2	1	1
IL84-HPVG-5Bx125-HX-SL-30		50	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx125-30	IL84-HPVG-5BSx125-30	50	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx175-30	IL84-HPVG-5BSx175-30	50	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx175-HX-SL-30		50	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx225-HX-SL-30		50	5/16-18	2	2-1/4	1
IL84-HPVG-6Bx1/4-30	IL84-HPVG-6BSx1/4-30	50	3/8-16	2	1/4	1
IL84-HPVG-6Bx1/2-30	IL84-HPVG-6BSx1/2-30	50	3/8-16	2	1/2	1
IL84-HPVG-6Bx1/2-HX-SL-30		50	3/8-16	2	1/2	1
IL84-HPVG-6Bx3/4-HX-SL-30		50	3/8-16	2	3/4	1
IL84-HPVG-6Bx1-30	IL84-HPVG-6BSx1-30	50	3/8-16	2	1	1
IL84-HPVG-6Bx1-HX-SL-30		50	3/8-16	2	1	1
IL84-HPVG-6Bx125-30	IL84-HPVG-6BSx125-30	50	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx125-HX-SL-30		50	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx150-30	IL84-HPVG-6BSx150-30	50	3/8-16	2	1-1/2	1
IL84-HPVG-6Bx175-HX-SL-30		50	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx175-30	IL84-HPVG-6BSx175-30	50	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx238-30	IL84-HPVG-6BSx238-30	50	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-SL-30		50	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-HX-SL-30		50	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx275-HX-SL-30		50	3/8-16	2	2-3/4	1
IL84-HPVG-6Bx338-HX-SL-30		50	3/8-16	2	3-3/8	1
IL84-HPVG-7Bx3/4-30	IL84-HPVG-7BSx3/4-30	50	1/2-13	2	3/4	1
IL84-HPVG-7Bx1-30	IL84-HPVG-7BSx1-30	50	1/2-13	2	1	1
IL84-HPVG-7Bx125-30	IL84-HPVG-7BSx125-30	50	1/2-13	2	1-1/4	1
IL84-HPVG-7Bx150-30	IL84-HPVG-7BSx150-30	50	1/2-13	2	1-1/2	1
IL84-HPVG-7Bx2-30	IL84-HPVG-7BSx2-30	50	1/2-13	2	2	1
IL84-HPVG-7Bx238-30		50	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx238-HX-30		50	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx278-30	IL84-HPVG-7BSx278-30	50	1/2-13	2	2-7/8	1
IL84-HPVG-7Bx3-HX-30		50	1/2-13	2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE	Standard-Flex® TPE	Firm-Flex® TPU	Hard-Flex® TPU	Stiff-Flex® TPU
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser)	Medium Hard (Wiper Blades)	Hard (Tire Tread)	Extra Hard (Skate Wheel)
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20	25 30 35	40 45 50	55 60 65 70	75 80 85	90 95 100

Copyright © 2019 IEC, Inc.



**Standard-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



Vibration Glide Bottom

**- Standard-Flex Hi-Pro Vibe-Glides® (45-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL82-HPVG-4Bx1/4-45	IL82-HPVG-4BSx1/4-45	75	1/4-20	1-1/2	1/4	1
IL82-HPVG-4Bx1/2-45	IL82-HPVG-4BSx1/2-45	75	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx1/2-HX-SL-45		75	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx3/4-45	IL82-HPVG-4BSx3/4-45	75	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx3/4-HX-SL-45		75	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx1-45	IL82-HPVG-4BSx1-45	75	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx1-HX-SL-45		75	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx125-45	IL82-HPVG-4BSx125-45	75	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx125-HX-SL-45		75	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx150-45	IL82-HPVG-4BSx150-45	75	1/4-20	1-1/2	1-1/2	1
IL82-HPVG-4Bx175-45	IL82-HPVG-4BSx175-45	75	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx175-HX-SL-45		75	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx2-45	IL82-HPVG-4BSx2-45	75	1/4-20	1-1/2	2	1
IL82-HPVG-4Bx275-45	IL82-HPVG-4BSx275-45	75	1/4-20	1-1/2	2-3/4	1
IL82-HPVG-5Bx1/4-45	IL82-HPVG-5BSx1/4-45	150	5/16-18	1-1/2	1/4	1
IL82-HPVG-5Bx1/2-45	IL82-HPVG-5BSx1/2-45	150	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx1/2-HX-SL-45		150	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx3/4-45	IL82-HPVG-5BSx3/4-45	150	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx3/4-HX-SL-45		150	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx1-45	IL82-HPVG-5BSx1-45	150	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx1-HX-SL-45		150	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx125-45	IL82-HPVG-5BSx125-45	150	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx175-45	IL82-HPVG-5BSx175-45	150	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx175-HX-SL-45		150	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx225-HX-SL-45		150	5/16-18	1-1/2	2-1/4	1
IL82-HPVG-6Bx1/4-45	IL82-HPVG-6BSx1/4-45	150	3/8-16	1-1/2	1/4	1
IL82-HPVG-6Bx1/2-45	IL82-HPVG-6BSx1/2-45	150	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx1/2-HX-SL-45		150	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx3/4-45	IL82-HPVG-6BSx3/4-45	150	3/8-16	1-1/2	3/4	1
IL82-HPVG-6Bx3/4-HX-SL-45		150	3/8-16	1-1/2	3/4	1
IL82-HPVG-6Bx1-45	IL82-HPVG-6BSx1-45	150	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx1-HX-SL-45		150	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx125-45	IL82-HPVG-6BSx125-45	150	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx125-HX-SL-45		150	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx150-45	IL82-HPVG-6BSx150-45	150	3/8-16	1-1/2	1-1/2	1
IL82-HPVG-6Bx175-HX-SL-45		150	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx175-45	IL82-HPVG-6BSx175-45	150	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx238-45	IL82-HPVG-6BSx238-45	150	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-SL-45		150	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-HX-SL-45		150	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx275-HX-SL-45		150	3/8-16	1-1/2	2-3/4	1
IL82-HPVG-6Bx338-HX-SL-45		150	3/8-16	1-1/2	3-3/8	1
IL82-HPVG-7Bx3/4-45	IL82-HPVG-7BSx3/4-45	150	1/2-13	1-1/2	3/4	1
IL82-HPVG-7Bx1-45	IL82-HPVG-7BSx1-45	150	1/2-13	1-1/2	1	1
IL82-HPVG-7Bx125-45	IL82-HPVG-7BSx125-45	150	1/2-13	1-1/2	1-1/4	1
IL82-HPVG-7Bx150-45	IL82-HPVG-7BSx150-45	150	1/2-13	1-1/2	1-1/2	1
IL82-HPVG-7Bx2-45	IL82-HPVG-7BSx2-45	150	1/2-13	1-1/2	2	1
IL82-HPVG-7Bx238-45		150	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx238-HX-45		150	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx278-45	IL82-HPVG-7BSx278-45	150	1/2-13	1-1/2	2-7/8	1
IL82-HPVG-7Bx3-HX-45		150	1/2-13	1-1/2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings	Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU	Hard-Flex® TPU	Stiff-Flex® TPU												
	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser) (Wiper Blades)			Hard (Tire Tread)	Extra Hard (Skate Wheel)												
<b>Type</b>																			
<b>Shore A</b> Rubber, Elastomer (TPE) & Urethane (TPU)	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100



**HI-PRO VIBE-GLIDES®**

**Standard-Flex Hi-Pro Vibe-Glides®**

1-1/2" to 2" BASE DIAMETER

**Standard-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



**- Standard-Flex Hi-Pro Vibe-Glides® (45-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL84-HPVG-4Bx1/4-45	IL84-HPVG-4BSx1/4-45	100	1/4-20	2	1/4	1
IL84-HPVG-4Bx1/2-45	IL84-HPVG-4BSx1/2-45	100	1/4-20	2	1/2	1
IL84-HPVG-4Bx1/2-HX-SL-45		100	1/4-20	2	1/2	1
IL84-HPVG-4Bx3/4-45	IL84-HPVG-4BSx3/4-45	100	1/4-20	2	3/4	1
IL84-HPVG-4Bx3/4-HX-SL-45		100	1/4-20	2	3/4	1
IL84-HPVG-4Bx1-45	IL84-HPVG-4BSx1-45	100	1/4-20	2	1	1
IL84-HPVG-4Bx1-HX-SL-45		100	1/4-20	2	1	1
IL84-HPVG-4Bx125-45	IL84-HPVG-4BSx125-45	100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx125-HX-SL-45		100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx150-45	IL84-HPVG-4BSx150-45	100	1/4-20	2	1-1/2	1
IL84-HPVG-4Bx175-45	IL84-HPVG-4BSx175-45	100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx175-HX-SL-45		100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx2-45	IL84-HPVG-4BSx2-45	100	1/4-20	2	2	1
IL84-HPVG-4Bx2-45	IL84-HPVG-4BSx2-45	100	1/4-20	2	2-3/4	1
IL84-HPVG-4Bx275-45	IL84-HPVG-4BSx275-45	200	5/16-18	2	1/4	1
IL84-HPVG-5Bx1/2-45	IL84-HPVG-5BSx1/2-45	200	5/16-18	2	1/2	1
IL84-HPVG-5Bx1/2-HX-SL-45		200	5/16-18	2	1/2	1
IL84-HPVG-5Bx3/4-45	IL84-HPVG-5BSx3/4-45	200	5/16-18	2	3/4	1
IL84-HPVG-5Bx3/4-HX-SL-45		200	5/16-18	2	3/4	1
IL84-HPVG-5Bx1-45	IL84-HPVG-5BSx1-45	200	5/16-18	2	1	1
IL84-HPVG-5Bx1-HX-SL-45		200	5/16-18	2	1	1
IL84-HPVG-5Bx125-45	IL84-HPVG-5BSx125-45	200	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx175-45	IL84-HPVG-5BSx175-45	200	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx175-HX-SL-45		200	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx225-HX-SL-45		200	5/16-18	2	2-1/4	1
IL84-HPVG-6Bx1/4-45	IL84-HPVG-6BSx1/4-45	200	3/8-16	2	1/4	1
IL84-HPVG-6Bx1/2-45	IL84-HPVG-6BSx1/2-45	200	3/8-16	2	1/2	1
IL84-HPVG-6Bx1/2-HX-SL-45		200	3/8-16	2	1/2	1
IL84-HPVG-6Bx3/4-HX-SL-45		200	3/8-16	2	3/4	1
IL84-HPVG-6Bx1-45	IL84-HPVG-6BSx1-45	200	3/8-16	2	1	1
IL84-HPVG-6Bx1-HX-SL-45		200	3/8-16	2	1	1
IL84-HPVG-6Bx125-45	IL84-HPVG-6BSx125-45	200	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx125-HX-SL-45		200	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx150-45	IL84-HPVG-6BSx150-45	200	3/8-16	2	1-1/2	1
IL84-HPVG-6Bx175-HX-SL-45		200	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx175-45	IL84-HPVG-6BSx175-45	200	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx238-45	IL84-HPVG-6BSx238-45	200	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-SL-45		200	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-HX-SL-45		200	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx275-HX-SL-45		200	3/8-16	2	2-3/4	1
IL84-HPVG-6Bx338-HX-SL-45		200	3/8-16	2	3-3/8	1
IL84-HPVG-7Bx3/4-45	IL84-HPVG-7BSx3/4-45	200	1/2-13	2	3/4	1
IL84-HPVG-7Bx1-45	IL84-HPVG-7BSx1-45	200	1/2-13	2	1	1
IL84-HPVG-7Bx125-45	IL84-HPVG-7BSx125-45	200	1/2-13	2	1-1/4	1
IL84-HPVG-7Bx150-45	IL84-HPVG-7BSx150-45	200	1/2-13	2	1-1/2	1
IL84-HPVG-7Bx2-45	IL84-HPVG-7BSx2-45	200	1/2-13	2	2	1
IL84-HPVG-7Bx238-45		200	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx238-HX-45		200	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx278-45	IL84-HPVG-7BSx278-45	200	1/2-13	2	2-7/8	1
IL84-HPVG-7Bx3-HX-45		200	1/2-13	2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU		Hard-Flex® TPU		Stiff-Flex® TPU	
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)		Medium Hard (Pink Eraser)		Medium Hard (Wiper Blades)		Hard (Tire Tread)		Extra Hard (Skate Wheel)	
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20	25	30	35 40 45 50 55	60 65 70	75 80 85	90 95 100				

Copyright © 2019 IEC, Inc.



**Firm-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



Vibration Glide Bottom

**- Firm-Flex Hi-Pro Vibe-Glides® (60-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL82-HPVG-4Bx1/4-60	IL82-HPVG-4BSx1/4-60	100	1/4-20	1-1/2	1/4	1
IL82-HPVG-4Bx1/2-60	IL82-HPVG-4BSx1/2-60	100	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx1/2-HX-SL-60		100	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx3/4-60	IL82-HPVG-4BSx3/4-60	100	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx3/4-HX-SL-60		100	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx1-60	IL82-HPVG-4BSx1-60	100	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx1-HX-SL-60		100	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx125-60	IL82-HPVG-4BSx125-60	100	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx125-HX-SL-60		100	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx150-60	IL82-HPVG-4BSx150-60	100	1/4-20	1-1/2	1-1/2	1
IL82-HPVG-4Bx175-60	IL82-HPVG-4BSx175-60	100	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx175-HX-SL-60		100	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx2-60	IL82-HPVG-4BSx2-60	100	1/4-20	1-1/2	2	1
IL82-HPVG-4Bx275-60	IL82-HPVG-4BSx275-60	100	1/4-20	1-1/2	2-3/4	1
IL82-HPVG-5Bx1/4-60	IL82-HPVG-5BSx1/4-60	250	5/16-18	1-1/2	1/4	1
IL82-HPVG-5Bx1/2-60	IL82-HPVG-5BSx1/2-60	250	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx1/2-HX-SL-60		250	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx3/4-60	IL82-HPVG-5BSx3/4-60	250	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx3/4-HX-SL-60		250	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx1-60	IL82-HPVG-5BSx1-60	250	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx1-HX-SL-60		250	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx125-60	IL82-HPVG-5BSx125-60	250	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx125-HX-SL-60		250	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx175-60	IL82-HPVG-5BSx175-60	250	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx175-HX-SL-60		250	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx225-HX-SL-60		250	5/16-18	1-1/2	2-1/4	1
IL82-HPVG-6Bx1/4-60	IL82-HPVG-6BSx1/4-60	250	3/8-16	1-1/2	1/4	1
IL82-HPVG-6Bx1/2-60	IL82-HPVG-6BSx1/2-60	250	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx1/2-HX-SL-60		250	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx3/4-HX-SL-60		250	3/8-16	1-1/2	3/4	1
IL82-HPVG-6Bx1-60	IL82-HPVG-6BSx1-60	250	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx1-HX-SL-60		250	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx125-60	IL82-HPVG-6BSx125-60	250	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx125-HX-SL-60		250	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx150-60	IL82-HPVG-6BSx150-60	250	3/8-16	1-1/2	1-1/2	1
IL82-HPVG-6Bx175-HX-SL-60		250	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx175-60	IL82-HPVG-6BSx175-60	250	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx238-60	IL82-HPVG-6BSx238-60	250	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-SL-60		250	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-HX-SL-60		250	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx275-HX-SL-60		250	3/8-16	1-1/2	2-3/4	1
IL82-HPVG-6Bx338-HX-SL-60		250	3/8-16	1-1/2	3-3/8	1
IL82-HPVG-7Bx3/4-60	IL82-HPVG-7BSx3/4-60	250	1/2-13	1-1/2	3/4	1
IL82-HPVG-7Bx1-60	IL82-HPVG-7BSx1-60	250	1/2-13	1-1/2	1	1
IL82-HPVG-7Bx125-60	IL82-HPVG-7BSx125-60	250	1/2-13	1-1/2	1-1/4	1
IL82-HPVG-7Bx150-60	IL82-HPVG-7BSx150-60	250	1/2-13	1-1/2	1-1/2	1
IL82-HPVG-7Bx2-60	IL82-HPVG-7BSx2-60	250	1/2-13	1-1/2	2	1
IL82-HPVG-7Bx238-60		250	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx238-HX-60		250	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx278-60	IL82-HPVG-7BSx278-60	250	1/2-13	1-1/2	2-7/8	1
IL82-HPVG-7Bx3-HX-60		250	1/2-13	1-1/2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU		Hard-Flex® TPU		Stiff-Flex® TPU									
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser)		Medium Hard (Wiper Blades)		Hard (Tire Tread)		Extra Hard (Skate Wheel)										
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100



**HI-PRO VIBE-GLIDES®**

**Firm-Flex Hi-Pro Vibe-Glides®**

1-1/2" to 2" BASE DIAMETER

**Firm-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



**- Firm-Flex Hi-Pro Vibe-Glides® (60-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL84-HPVG-4Bx1/4-60	IL84-HPVG-4BSx1/4-60	100	1/4-20	2	1/4	1
IL84-HPVG-4Bx1/2-60	IL84-HPVG-4BSx1/2-60	100	1/4-20	2	1/2	1
IL84-HPVG-4Bx1/2-HX-SL-60		100	1/4-20	2	1/2	1
IL84-HPVG-4Bx3/4-60	IL84-HPVG-4BSx3/4-60	100	1/4-20	2	3/4	1
IL84-HPVG-4Bx3/4-HX-SL-60		100	1/4-20	2	3/4	1
IL84-HPVG-4Bx1-60	IL84-HPVG-4BSx1-60	100	1/4-20	2	1	1
IL84-HPVG-4Bx1-HX-SL-60		100	1/4-20	2	1	1
IL84-HPVG-4Bx125-60	IL84-HPVG-4BSx125-60	100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx125-HX-SL-60		100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx1300-60	IL84-HPVG-4BSx1300-60	100	1/4-20	2	1-1/2	1
IL84-HPVG-4Bx175-60	IL84-HPVG-4BSx175-60	100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx175-HX-SL-60		100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx2-60	IL84-HPVG-4BSx2-60	100	1/4-20	2	2	1
IL84-HPVG-4Bx275-60	IL84-HPVG-4BSx275-60	100	1/4-20	2	2-3/4	1
IL84-HPVG-5Bx1/4-60	IL84-HPVG-5BSx1/4-60	300	5/16-18	2	1/4	1
IL84-HPVG-5Bx1/2-60	IL84-HPVG-5BSx1/2-60	300	5/16-18	2	1/2	1
IL84-HPVG-5Bx1/2-HX-SL-60		300	5/16-18	2	1/2	1
IL84-HPVG-5Bx3/4-60	IL84-HPVG-5BSx3/4-60	300	5/16-18	2	3/4	1
IL84-HPVG-5Bx3/4-HX-SL-60		300	5/16-18	2	3/4	1
IL84-HPVG-5Bx1-60	IL84-HPVG-5BSx1-60	300	5/16-18	2	1	1
IL84-HPVG-5Bx1-HX-SL-60		300	5/16-18	2	1	1
IL84-HPVG-5Bx125-60	IL84-HPVG-5BSx125-60	300	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx175-60	IL84-HPVG-5BSx175-60	300	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx175-HX-SL-60		300	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx225-HX-SL-60		300	5/16-18	2	2-1/4	1
IL84-HPVG-6Bx1/4-60	IL84-HPVG-6BSx1/4-60	300	3/8-16	2	1/4	1
IL84-HPVG-6Bx1/2-60	IL84-HPVG-6BSx1/2-60	300	3/8-16	2	1/2	1
IL84-HPVG-6Bx1/2-HX-SL-60		300	3/8-16	2	1/2	1
IL84-HPVG-6Bx3/4-HX-SL-60		300	3/8-16	2	3/4	1
IL84-HPVG-6Bx1-60	IL84-HPVG-6BSx1-60	300	3/8-16	2	1	1
IL84-HPVG-6Bx1-HX-SL-60		300	3/8-16	2	1	1
IL84-HPVG-6Bx125-60	IL84-HPVG-6BSx125-60	300	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx125-HX-SL-60		300	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx1300-60	IL84-HPVG-6BSx1300-60	300	3/8-16	2	1-1/2	1
IL84-HPVG-6Bx175-HX-SL-60		300	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx175-60	IL84-HPVG-6BSx175-60	300	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx238-60	IL84-HPVG-6BSx238-60	300	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-SL-60		300	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-HX-SL-60		300	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx275-HX-SL-60		300	3/8-16	2	2-3/4	1
IL84-HPVG-6Bx338-HX-SL-60		300	3/8-16	2	3-3/8	1
IL84-HPVG-7Bx3/4-60	IL84-HPVG-7BSx3/4-60	300	1/2-13	2	3/4	1
IL84-HPVG-7Bx1-60	IL84-HPVG-7BSx1-60	300	1/2-13	2	1	1
IL84-HPVG-7Bx125-60	IL84-HPVG-7BSx125-60	300	1/2-13	2	1-1/4	1
IL84-HPVG-7Bx150-60	IL84-HPVG-7BSx150-60	300	1/2-13	2	1-1/2	1
IL84-HPVG-7Bx2-60	IL84-HPVG-7BSx2-60	300	1/2-13	2	2	1
IL84-HPVG-7Bx238-60		300	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx238-HX-60		300	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx278-60	IL84-HPVG-7BSx278-60	300	1/2-13	2	2-7/8	1
IL84-HPVG-7Bx3-HX-60		300	1/2-13	2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings	Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU		Hard-Flex® TPU		Stiff-Flex® TPU										
Type	Soft (Mouse Pad)		Medium Hard (Pink Eraser)		Medium Hard (Wiper Blades)		Hard (Tire Tread)		Extra Hard (Skate Wheel)										
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100

Copyright © 2019, IEC, Inc.



**Hard-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



Vibration Glide Bottom

**- Hard-Flex Hi-Pro Vibe-Glides® (75-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL82-HPVG-4Bx1/4-75	IL82-HPVG-4BSx1/4-75	100	1/4-20	1-1/2	1/4	1
IL82-HPVG-4Bx1/2-75	IL82-HPVG-4BSx1/2-75	100	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx1/2-HX-SL-75		100	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx3/4-75	IL82-HPVG-4BSx3/4-75	100	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx3/4-HX-SL-75		100	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx1-75	IL82-HPVG-4BSx1-75	100	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx1-HX-SL-75		100	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx125-75	IL82-HPVG-4BSx125-75	100	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx125-HX-SL-75		100	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx150-75	IL82-HPVG-4BSx150-75	100	1/4-20	1-1/2	1-1/2	1
IL82-HPVG-4Bx175-75	IL82-HPVG-4BSx175-75	100	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx175-HX-SL-75		100	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx2-75	IL82-HPVG-4BSx2-75	100	1/4-20	1-1/2	2	1
IL82-HPVG-4Bx275-75	IL82-HPVG-4BSx275-75	100	1/4-20	1-1/2	2-3/4	1
IL82-HPVG-5Bx1/4-75	IL82-HPVG-5BSx1/4-75	400	5/16-18	1-1/2	1/4	1
IL82-HPVG-5Bx1/2-75	IL82-HPVG-5BSx1/2-75	400	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx1/2-HX-SL-75		400	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx3/4-75	IL82-HPVG-5BSx3/4-75	400	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx3/4-HX-SL-75		400	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx1-75	IL82-HPVG-5BSx1-75	400	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx1-HX-SL-75		400	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx125-75	IL82-HPVG-5BSx125-75	400	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx175-75	IL82-HPVG-5BSx175-75	400	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx175-HX-SL-75		400	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx225-HX-SL-75		400	5/16-18	1-1/2	2-1/4	1
IL82-HPVG-6Bx1/4-75	IL82-HPVG-6BSx1/4-75	400	3/8-16	1-1/2	1/4	1
IL82-HPVG-6Bx1/2-75	IL82-HPVG-6BSx1/2-75	400	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx1/2-HX-SL-75		400	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx3/4-HX-SL-75		400	3/8-16	1-1/2	3/4	1
IL82-HPVG-6Bx1-75	IL82-HPVG-6BSx1-75	400	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx1-HX-SL-75		400	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx125-75	IL82-HPVG-6BSx125-75	400	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx125-HX-SL-75		400	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx150-75	IL82-HPVG-6BSx150-75	400	3/8-16	1-1/2	1-1/2	1
IL82-HPVG-6Bx175-HX-SL-75		400	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx175-75	IL82-HPVG-6BSx175-75	400	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx238-75	IL82-HPVG-6BSx238-75	400	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-SL-75		400	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-HX-SL-75		400	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx275-HX-SL-75		400	3/8-16	1-1/2	2-3/4	1
IL82-HPVG-6Bx338-HX-SL-75		400	3/8-16	1-1/2	3-3/8	1
IL82-HPVG-7Bx3/4-75	IL82-HPVG-7BSx3/4-75	400	1/2-13	1-1/2	3/4	1
IL82-HPVG-7Bx1-75	IL82-HPVG-7BSx1-75	400	1/2-13	1-1/2	1	1
IL82-HPVG-7Bx125-75	IL82-HPVG-7BSx125-75	400	1/2-13	1-1/2	1-1/4	1
IL82-HPVG-7Bx150-75	IL82-HPVG-7BSx150-75	400	1/2-13	1-1/2	1-1/2	1
IL82-HPVG-7Bx2-75	IL82-HPVG-7BSx2-75	400	1/2-13	1-1/2	2	1
IL82-HPVG-7Bx238-75		400	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx238-HX-75		400	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx278-75	IL82-HPVG-7BSx278-75	400	1/2-13	1-1/2	2-7/8	1
IL82-HPVG-7Bx3-HX-75		400	1/2-13	1-1/2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE	Standard-Flex® TPE	Firm-Flex® TPU	Hard-Flex® TPU	Stiff-Flex® TPU
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser) (Wiper Blades)		Hard (Tire Tread)	Extra Hard (Skate Wheel)
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20 25 30 35	30 35	40 45 50 55 60 65 70	75 80 85 90 95 100		

Copyright © 2019 IEC, Inc.



**HI-PRO VIBE-GLIDES®**

**Hard-Flex Hi-Pro Vibe-Glides®**

1-1/2" to 2" BASE DIAMETER

**Hard-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



**- Hard-Flex Hi-Pro Vibe-Glides® (75-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL84-HPVG-4Bx1/4-75	IL84-HPVG-4BSx1/4-75	100	1/4-20	2	1/4	1
IL84-HPVG-4Bx1/2-75	IL84-HPVG-4BSx1/2-75	100	1/4-20	2	1/2	1
IL84-HPVG-4Bx1/2-HX-SL-75		100	1/4-20	2	1/2	1
IL84-HPVG-4Bx3/4-75	IL84-HPVG-4BSx3/4-75	100	1/4-20	2	3/4	1
IL84-HPVG-4Bx3/4-HX-SL-75		100	1/4-20	2	3/4	1
IL84-HPVG-4Bx1-75	IL84-HPVG-4BSx1-75	100	1/4-20	2	1	1
IL84-HPVG-4Bx1-HX-SL-75		100	1/4-20	2	1	1
IL84-HPVG-4Bx125-75	IL84-HPVG-4BSx125-75	100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx125-HX-SL-75		100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx150-75	IL84-HPVG-4BSx150-75	100	1/4-20	2	1-1/2	1
IL84-HPVG-4Bx175-75	IL84-HPVG-4BSx175-75	100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx175-HX-SL-75		100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx2-75	IL84-HPVG-4BSx2-75	100	1/4-20	2	2	1
IL84-HPVG-4Bx2-75-75	IL84-HPVG-4BSx2-75-75	100	1/4-20	2	2-3/4	1
IL84-HPVG-5Bx1/4-75	IL84-HPVG-5BSx1/4-75	500	5/16-18	2	1/4	1
IL84-HPVG-5Bx1/2-75	IL84-HPVG-5BSx1/2-75	500	5/16-18	2	1/2	1
IL84-HPVG-5Bx1/2-HX-SL-75		500	5/16-18	2	1/2	1
IL84-HPVG-5Bx3/4-75	IL84-HPVG-5BSx3/4-75	500	5/16-18	2	3/4	1
IL84-HPVG-5Bx3/4-HX-SL-75		500	5/16-18	2	3/4	1
IL84-HPVG-5Bx1-75	IL84-HPVG-5BSx1-75	500	5/16-18	2	1	1
IL84-HPVG-5Bx1-HX-SL-75		500	5/16-18	2	1	1
IL84-HPVG-5Bx125-HX-SL-75		500	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx125-75	IL84-HPVG-5BSx125-75	500	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx175-75	IL84-HPVG-5BSx175-75	500	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx175-HX-SL-75		500	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx225-HX-SL-75		500	5/16-18	2	2-1/4	1
IL84-HPVG-6Bx1/4-75	IL84-HPVG-6BSx1/4-75	500	3/8-16	2	1/4	1
IL84-HPVG-6Bx1/2-75	IL84-HPVG-6BSx1/2-75	500	3/8-16	2	1/2	1
IL84-HPVG-6Bx1/2-HX-SL-75		500	3/8-16	2	1/2	1
IL84-HPVG-6Bx3/4-HX-SL-75		500	3/8-16	2	3/4	1
IL84-HPVG-6Bx1-75	IL84-HPVG-6BSx1-75	500	3/8-16	2	1	1
IL84-HPVG-6Bx1-HX-SL-75		500	3/8-16	2	1	1
IL84-HPVG-6Bx125-75	IL84-HPVG-6BSx125-75	500	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx125-HX-SL-75		500	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx150-75	IL84-HPVG-6BSx150-75	500	3/8-16	2	1-1/2	1
IL84-HPVG-6Bx175-HX-SL-75		500	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx175-75	IL84-HPVG-6BSx175-75	500	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx238-75	IL84-HPVG-6BSx238-75	500	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-SL-75		500	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-HX-SL-75		500	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx275-HX-SL-75		500	3/8-16	2	2-3/4	1
IL84-HPVG-6Bx338-HX-SL-75		500	3/8-16	2	3-3/8	1
IL84-HPVG-7Bx3/4-75	IL84-HPVG-7BSx3/4-75	500	1/2-13	2	3/4	1
IL84-HPVG-7Bx1-75	IL84-HPVG-7BSx1-75	500	1/2-13	2	1	1
IL84-HPVG-7Bx125-75	IL84-HPVG-7BSx125-75	500	1/2-13	2	1-1/4	1
IL84-HPVG-7Bx150-75	IL84-HPVG-7BSx150-75	500	1/2-13	2	1-1/2	1
IL84-HPVG-7Bx2-75	IL84-HPVG-7BSx2-75	500	1/2-13	2	2	1
IL84-HPVG-7Bx238-75		500	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx238-HX-75		500	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx278-75	IL84-HPVG-7BSx278-75	500	1/2-13	2	2-7/8	1
IL84-HPVG-7Bx3-HX-75		500	1/2-13	2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE	Standard-Flex® TPE	Firm-Flex® TPU	Hard-Flex® TPU	Stiff-Flex® TPU
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser)	Medium Hard (Wiper Blades)	Hard (Tire Tread)	Extra Hard (Skate Wheel)
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20 25 30 35	30 35	40 45 50 55 60 65 70	60 65 70	75 80 85	90 95 100

Copyright © 2019 IEC, Inc.





**Stiff-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



Vibration Glide Bottom

**- Stiff-Flex Hi-Pro Vibe-Glides® (90-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL82-HPVG-4Bx1/4-90	IL82-HPVG-4BSx1/4-90	100	1/4-20	1-1/2	1/4	1
IL82-HPVG-4Bx1/2-90	IL82-HPVG-4BSx1/2-90	100	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx1/2-HX-SL-90		100	1/4-20	1-1/2	1/2	1
IL82-HPVG-4Bx3/4-90	IL82-HPVG-4BSx3/4-90	100	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx3/4-HX-SL-90		100	1/4-20	1-1/2	3/4	1
IL82-HPVG-4Bx1-90	IL82-HPVG-4BSx1-90	100	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx1-HX-SL-90		100	1/4-20	1-1/2	1	1
IL82-HPVG-4Bx125-90	IL82-HPVG-4BSx125-90	100	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx125-HX-SL-90		100	1/4-20	1-1/2	1-1/4	1
IL82-HPVG-4Bx150-90	IL82-HPVG-4BSx150-90	100	1/4-20	1-1/2	1-1/2	1
IL82-HPVG-4Bx175-90	IL82-HPVG-4BSx175-90	100	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx175-HX-SL-90		100	1/4-20	1-1/2	1-3/4	1
IL82-HPVG-4Bx2-90	IL82-HPVG-4BSx2-90	100	1/4-20	1-1/2	2	1
IL82-HPVG-4Bx275-90	IL82-HPVG-4BSx275-90	100	1/4-20	1-1/2	2-3/4	1
IL82-HPVG-5Bx1/4-90	IL82-HPVG-5BSx1/4-90	500	5/16-18	1-1/2	1/4	1
IL82-HPVG-5Bx1/2-90	IL82-HPVG-5BSx1/2-90	500	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx1/2-HX-SL-90		500	5/16-18	1-1/2	1/2	1
IL82-HPVG-5Bx3/4-90	IL82-HPVG-5BSx3/4-90	500	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx3/4-HX-SL-90		500	5/16-18	1-1/2	3/4	1
IL82-HPVG-5Bx1-90	IL82-HPVG-5BSx1-90	500	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx1-HX-SL-90		500	5/16-18	1-1/2	1	1
IL82-HPVG-5Bx125-90	IL82-HPVG-5BSx125-90	500	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx125-HX-SL-90		500	5/16-18	1-1/2	1-1/4	1
IL82-HPVG-5Bx175-90	IL82-HPVG-5BSx175-90	500	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx175-HX-SL-90		500	5/16-18	1-1/2	1-3/4	1
IL82-HPVG-5Bx225-HX-SL-90		500	5/16-18	1-1/2	2-1/4	1
IL82-HPVG-6Bx1/4-90	IL82-HPVG-6BSx1/4-90	500	3/8-16	1-1/2	1/4	1
IL82-HPVG-6Bx1/2-90	IL82-HPVG-6BSx1/2-90	500	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx1/2-HX-SL-90		500	3/8-16	1-1/2	1/2	1
IL82-HPVG-6Bx3/4-HX-SL-90		500	3/8-16	1-1/2	3/4	1
IL82-HPVG-6Bx1-90	IL82-HPVG-6BSx1-90	500	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx1-HX-SL-90		500	3/8-16	1-1/2	1	1
IL82-HPVG-6Bx125-90	IL82-HPVG-6BSx125-90	500	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx125-HX-SL-90		500	3/8-16	1-1/2	1-1/4	1
IL82-HPVG-6Bx150-90	IL82-HPVG-6BSx150-90	500	3/8-16	1-1/2	1-1/2	1
IL82-HPVG-6Bx175-HX-SL-90		500	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx175-90	IL82-HPVG-6BSx175-90	500	3/8-16	1-1/2	1-3/4	1
IL82-HPVG-6Bx238-90	IL82-HPVG-6BSx238-90	500	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-SL-90		500	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx238-HX-SL-90		500	3/8-16	1-1/2	2-3/8	1
IL82-HPVG-6Bx275-HX-SL-90		500	3/8-16	1-1/2	2-3/4	1
IL82-HPVG-6Bx338-HX-SL-90		500	3/8-16	1-1/2	3-3/8	1
IL82-HPVG-7Bx3/4-90	IL82-HPVG-7BSx3/4-90	500	1/2-13	1-1/2	3/4	1
IL82-HPVG-7Bx1-90	IL82-HPVG-7BSx1-90	500	1/2-13	1-1/2	1	1
IL82-HPVG-7Bx125-90	IL82-HPVG-7BSx125-90	500	1/2-13	1-1/2	1-1/4	1
IL82-HPVG-7Bx150-90	IL82-HPVG-7BSx150-90	500	1/2-13	1-1/2	1-1/2	1
IL82-HPVG-7Bx2-90	IL82-HPVG-7BSx2-90	500	1/2-13	1-1/2	2	1
IL82-HPVG-7Bx238-90		500	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx238-HX-90		500	1/2-13	1-1/2	2-3/8	1
IL82-HPVG-7Bx278-90	IL82-HPVG-7BSx278-90	500	1/2-13	1-1/2	2-7/8	1
IL82-HPVG-7Bx3-HX-90		500	1/2-13	1-1/2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings	Soft-Flex® TPE		Standard-Flex® TPE		Firm-Flex® TPU	Hard-Flex® TPU	Stiff-Flex® TPU
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser) (Wiper Blades)			Hard (Tire Tread)	Extra Hard (Skate Wheel)
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20	25 30 35	40 45 50	55 60 65 70	75 80 85	90 95 100	



**HI-PRO VIBE-GLIDES®**

**Stiff-Flex Hi-Pro Vibe-Glides®**

1-1/2" to 2" BASE DIAMETER

**Stiff-Flex Hi-Pro Stud Vibe-Glides®**

The IEC *high-profile fixed stud* Vibe-Glide (Patent pending) features IEC's Ridge-Grip® design and are ideal for vibration and noise dampening, anti-skid, anti-marring and electrical isolation applications. Especially useful for raising and isolating electronic equipment, appliances, scales, audio and video equipment, optics, furniture, displays, racks, instruments, and for automotive, medical, fitness, marine, machinery, hotel and restaurant and HVAC applications. IEC's unique vibration design features a series of inner rings of varying heights and thicknesses to provide superior vibration dampening and stability in a compact form. The high-profile feature aids cleaning, ventilation, inspection and equipment isolation.

Available in multiple materials including Urethane (TPU), Elastomer (TPE), and Polypropylene (non-vibration dampening). TPU and TPE can be made with differing shore (-A) hardness (durometer) in order to achieve the appropriate combination of load support rating and vibration dampening effectiveness. Our standard offerings are listed here. Available in two base diameters, 1-1/2" and 2". **The load rating shown is based on the weight distribution being applied to the thread. If equipment is resting directly on the base, the load rating is 3x higher. The 1/4-20 load rating is lower than the other thread sizes due to the smaller bolt head size molded into the flexible base. The 2" base has a higher load rating due to the thicker ring sizes on the bottom of the flexible base.**


The steel stud has trivalent clear zinc plating. Also available with a steel female socket with 1/2-13 or 3/8-16 thread, or a thru-hole to fit a 5/16" or smaller screw to attach to your equipment or furniture. The base can be produced in various colors (brown, tan, gray, etc.) upon request. Just let us know your requirements and we will work with you.

**Features**

- Vibration dampening rubber bases
- Ridge-Grip® base design
- Loads to 1500 lbs
- Steel and Stainless studs
- Anti-skid and anti-marr
- Electrical isolation
- Corrosion resistant
- RoHS compliant
- Top hex and slot options

**Applications**

- Scales
- Audio and video equipment
- Appliances
- Instruments
- Furniture
- HVAC
- Stages
- Electronic and medical equipment
- Enclosures
- Racks
- Conveyors
- Fitness equipment
- Machinery
- Work Tables
- Displays
- Kitchen equipment



Top Hex (-HX) and Slot (-SL)



**- Stiff-Flex Hi-Pro Vibe-Glides® (90-A Durometer) -**

Steel	Stainless Steel	Load	Thread	A	B	C
<b>Steel and Stainless Steel High Profile Fixed Stud Vibration Glides</b>						
IL84-HPVG-4Bx1/4-90	IL84-HPVG-4BSx1/4-90	100	1/4-20	2	1/4	1
IL84-HPVG-4Bx1/2-90	IL84-HPVG-4BSx1/2-90	100	1/4-20	2	1/2	1
IL84-HPVG-4Bx1/2-HX-SL-90		100	1/4-20	2	1/2	1
IL84-HPVG-4Bx3/4-90	IL84-HPVG-4BSx3/4-90	100	1/4-20	2	3/4	1
IL84-HPVG-4Bx3/4-HX-SL-90		100	1/4-20	2	3/4	1
IL84-HPVG-4Bx1-90	IL84-HPVG-4BSx1-90	100	1/4-20	2	1	1
IL84-HPVG-4Bx1-HX-SL-90		100	1/4-20	2	1	1
IL84-HPVG-4Bx125-90	IL84-HPVG-4BSx125-90	100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx125-HX-SL-90		100	1/4-20	2	1-1/4	1
IL84-HPVG-4Bx150-90	IL84-HPVG-4BSx150-90	100	1/4-20	2	1-1/2	1
IL84-HPVG-4Bx175-90	IL84-HPVG-4BSx175-90	100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx175-HX-SL-90		100	1/4-20	2	1-3/4	1
IL84-HPVG-4Bx2-90	IL84-HPVG-4BSx2-90	100	1/4-20	2	2	1
IL84-HPVG-4Bx275-90	IL84-HPVG-4BSx275-90	100	1/4-20	2	2-3/4	1
IL84-HPVG-5Bx1/4-90	IL84-HPVG-5BSx1/4-90	600	5/16-18	2	1/4	1
IL84-HPVG-5Bx1/2-90	IL84-HPVG-5BSx1/2-90	600	5/16-18	2	1/2	1
IL84-HPVG-5Bx1/2-HX-SL-90		600	5/16-18	2	1/2	1
IL84-HPVG-5Bx3/4-90	IL84-HPVG-5BSx3/4-90	600	5/16-18	2	3/4	1
IL84-HPVG-5Bx3/4-HX-SL-90		600	5/16-18	2	3/4	1
IL84-HPVG-5Bx1-90	IL84-HPVG-5BSx1-90	600	5/16-18	2	1	1
IL84-HPVG-5Bx1-HX-SL-90		600	5/16-18	2	1	1
IL84-HPVG-5Bx125-90	IL84-HPVG-5BSx125-90	600	5/16-18	2	1-1/4	1
IL84-HPVG-5Bx175-90	IL84-HPVG-5BSx175-90	600	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx175-HX-SL-90		600	5/16-18	2	1-3/4	1
IL84-HPVG-5Bx225-HX-SL-90		600	5/16-18	2	2-1/4	1
IL84-HPVG-6Bx1/4-90	IL84-HPVG-6BSx1/4-90	600	3/8-16	2	1/4	1
IL84-HPVG-6Bx1/2-90	IL84-HPVG-6BSx1/2-90	600	3/8-16	2	1/2	1
IL84-HPVG-6Bx1/2-HX-SL-90		600	3/8-16	2	1/2	1
IL84-HPVG-6Bx3/4-HX-SL-90		600	3/8-16	2	3/4	1
IL84-HPVG-6Bx1-90	IL84-HPVG-6BSx1-90	600	3/8-16	2	1	1
IL84-HPVG-6Bx1-HX-SL-90		600	3/8-16	2	1	1
IL84-HPVG-6Bx125-90	IL84-HPVG-6BSx125-90	600	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx125-HX-SL-90		600	3/8-16	2	1-1/4	1
IL84-HPVG-6Bx150-90	IL84-HPVG-6BSx150-90	600	3/8-16	2	1-1/2	1
IL84-HPVG-6Bx175-HX-SL-90		600	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx175-90	IL84-HPVG-6BSx175-90	600	3/8-16	2	1-3/4	1
IL84-HPVG-6Bx238-90	IL84-HPVG-6BSx238-90	600	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-SL-90		600	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx238-HX-SL-90		600	3/8-16	2	2-3/8	1
IL84-HPVG-6Bx275-HX-SL-90		600	3/8-16	2	2-3/4	1
IL84-HPVG-6Bx338-HX-SL-90		600	3/8-16	2	3-3/8	1
IL84-HPVG-7Bx3/4-90	IL84-HPVG-7BSx3/4-90	600	1/2-13	2	3/4	1
IL84-HPVG-7Bx1-90	IL84-HPVG-7BSx1-90	600	1/2-13	2	1	1
IL84-HPVG-7Bx125-90	IL84-HPVG-7BSx125-90	600	1/2-13	2	1-1/4	1
IL84-HPVG-7Bx150-90	IL84-HPVG-7BSx150-90	600	1/2-13	2	1-1/2	1
IL84-HPVG-7Bx2-90	IL84-HPVG-7BSx2-90	600	1/2-13	2	2	1
IL84-HPVG-7Bx238-90		600	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx238-HX-90		600	1/2-13	2	2-3/8	1
IL84-HPVG-7Bx278-90	IL84-HPVG-7BSx278-90	600	1/2-13	2	2-7/8	1
IL84-HPVG-7Bx3-HX-90		600	1/2-13	2	3	1

IEC Vibe-Glide® TPE & TPU standard offerings		Soft-Flex® TPE	Standard-Flex® TPE	Firm-Flex® TPU	Hard-Flex® TPU	Stiff-Flex® TPU
Type	Soft (Mouse Pad)	Medium Soft (Bottle Nipple)	Medium Hard (Pink Eraser) (Wiper Blades)		Hard (Tire Tread)	Extra Hard (Skate Wheel)
Shore A Rubber, Elastomer (TPE) & Urethane (TPU)	10 15 20	25 30 35	40 45 50 55	60 65 70	75 80 85	90 95 100

Copyright © 2019 IEC, Inc.